



Bearing No. 51415

C	254
r	2
d	75 mm
D	160 mm
T	65 mm
D_	160
Z_	10
B_	65
ra	2
C0	560
da	125
D1	78 mm
d1	160 mm
T_	65
DA_	30.162
SRI	16.3
D_1	78
D_a	110
SRE	16.3
SREN	0
yobi	51415
SRIN	0
SRIX	0.125
mass	6.15
SDM_	117.5
SREX	0.125
KBRG	5111
Noun	Bearing
Weight	6,15 Kg
Height	2.559 Inch 65

	Millimeter
LangID	1
r min.	2 mm
UNSPSC	31171552
Banded	No
Bore 2	3.071 Inch 78 Millimeter
Bore 1	2.953 Inch 75 Millimeter
da min.	125 mm
Oil rpm	1400
Da max.	110 mm
hidYobi	51415
ra max.	2 mm
GRS rpm	950
hidTable	ecat_NSSDTB
Category	Thrust Ball Bearings
Inventory	0.0
Size (mm)	75x160x65
Width (mm)	65
Prod_Type3	TB_SD_WFS
Weight / LBS	13.55843
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
Bearing number	51415
Other Features	Single Row With Flat Seat
Keyword String	Ball Thrust
Thrust Bearing	Yes
Precision Class	Non-Precision
Rolling Element	Ball Bearing
Manufacturer URL	http://www.nskamericas.com

	com
Long Description	75MM Bore 1; 78MM Bore 2; 160MM Outside Diameter; 65MM Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; Non-Precision
Outside Diameter	6.299 Inch 160 Millimeter
Weight / Kilogram	6.35
Manufacturer Name	NSK
Bore Diameter (mm)	75
Outer Diameter (mm)	160
Minimum Buy Quantity	N/A
Component Description	Roller Assembly Plus Raceways
Harmonized Tariff Code	8482.10.50.08
Single or Double Direction	Single Direction
(Grease) Lubrication Speed	950 r/min
Basic static load rating (C0)	560 kN
Basic dynamic load rating (C)	254 kN
Overall Height with Aligning Washer	0 Inch 0 Millimeter