



**Bearing No. 51415**

D	160 mm
d	75 mm
T	65 mm
d1	160 mm
D1	78 mm
Noun	Bearing
Bore 2	3.071 Inch   78 Millimeter
Weight	5,97 Kg
Bore 1	2.953 Inch   75 Millimeter
UNSPSC	31171552
Banded	No
r min.	2 mm
Height	2.559 Inch   65 Millimeter
da min.	125 mm
ra max.	2 mm
Da max.	110 mm
series:	514
Category	Thrust Ball Bearings
Inventory	0.0
Size (mm)	75x160x65
Width (mm)	65
Weight / LBS	13.1616
maximum rpm:	1400 rpm
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
bore diameter:	75 mm
overall width:	65 mm

Keyword String	Ball Thrust
cage material:	Steel
fillet radius:	2 mm
Bearing number	51415
Other Features	Single Row   With Flat Seat
Thrust Bearing	Yes
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Long Description	75MM Bore 1; 78MM Bore 2; 160MM Outside Diameter; 65MM Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; ABEC 1   ISO P0 Precision
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Outside Diameter	6.299 Inch   160 Millimeter
outside diameter:	160 mm
Manufacturer Name	NTN
Weight / Kilogram	5.97
bearing material:	High Carbon Chrome Steel
precision rating:	ISO Class 0
Bore Diameter (mm)	75
Outer Diameter (mm)	160
thrust bearing type:	Single-Direction
Minimum Buy Quantity	N/A
separable or banded:	Separable
Component Description	Roller Assembly Plus Raceways
static load capacity:	615000 N
dynamic load capacity:	269000 N
Harmonized Tariff Code	8482.10.50.08

Manufacturer Item Number	51415
outside diameter design:	Straight
(Grease) Lubrication Speed	940 r/min
Single or Double Direction	Single Direction
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	615 kN
Basic dynamic load rating (C)	269 kN
Overall Height with Aligning Washer	0 Inch   0 Millimeter