



Bearing No. 22313EAE4

| | |
|------|-------------------------------|
| e | 0.34 |
| d | 65 mm |
| B | 48 mm |
| D | 140 mm |
| C | 48 mm |
| r | 2.1 |
| Y2 | 3 |
| D_ | 140 |
| Y1 | 2 |
| Z_ | 16 |
| B_ | 48 |
| Y0 | 2 |
| ra | 2 |
| C0 | 380 |
| X0 | 1 |
| X1 | 1 |
| X2 | 0.67 |
| Y3 | 2 |
| DI_ | 87.838 |
| DA_ | 18.6 |
| HPS | HPS |
| SIR | 19.53 |
| DE_ | 124.145 |
| mass | 3.52 |
| ALP3 | 0 |
| ALP1 | 12 |
| ALP2 | 35 |
| Bore | 2.559 Inch 65 Millimeter |
| SDM_ | 105.991 |
| | |

| | |
|------------|---------------------------|
| bomp | 22313EAE4 |
| SBRG | 23 |
| KBRG | 2328 |
| yobi | 22313EAE4 |
| Noun | Bearing |
| Width | 1.89 Inch 48 Millimeter |
| UNSPSC | 31171510 |
| da max | 84 mm |
| Da min | 119 mm |
| da min | 77 |
| ALPHA_ | 0.22 |
| Weight | 3,52 Kg |
| LangID | 1 |
| r min. | 2,1 mm |
| ra max. | 2 mm |
| da min. | 77 mm |
| Da max. | 128 mm |
| D_a min | 119 |
| series: | 223 |
| TSR rpm | 3800 |
| D_a max | 128 |
| hidYobi | 22313EAE4 |
| GRS rpm | 3200 |
| Oil rpm | 4000 |
| hidTable | ecat_NSSPHR |
| Category | Spherical Roller Bearing |
| Size (mm) | 65x140x48 |
| Inventory | 0.0 |
| Macha rpm | 5000 |
| Enclosure | Open |
| bore type: | Straight |
| Prod_Type3 | SRB_CTB_CB |
| | |

| | |
|-------------------|--|
| cage type: | Inner Ring Guided |
| Width (mm) | 48 |
| maximum rpm: | 4000 RPM |
| Bore Profile | Straight |
| Weight / LBS | 0 |
| Inch - Metric | Metric |
| closure type: | Open |
| Cage Material | Steel |
| Product Group | B04311 |
| Bearing number | 22313EAE4 |
| overall width: | 48 mm |
| bore diameter: | 65 mm |
| Relubricatable | Yes |
| fillet radius: | 2.1 mm |
| Keyword String | Spherical |
| cage material: | Steel |
| Mounting Method | Shaft Mount |
| Rolling Element | Spherical Roller Bearing |
| finish/coating: | Uncoated |
| Manufacturer URL | http://www.nskamericas.com |
| Outside Diameter | 5.512 Inch 140 Millimeter |
| Long Description | 65MM Straight Bore; 140MM Outside Diameter; 48MM Width; C0-Medium Clearance; Shaft Mount; Double Row of Spherical Roller Bearings; Steel Cage Material; Open Enclosure; Relubricatable |
| outer ring type: | Not Split |
| outside diameter: | 140 mm |
| Withdrawal Sleeve | Not Applicable |

| | |
|-------------------------------|---|
| bearing material: | Steel |
| Manufacturer Name | NSK |
| Weight / Kilogram | 3.58 |
| outer ring width: | 48 mm |
| precision rating: | RBEC 1 (ISO Class Normal) |
| Bore Diameter (mm) | 65 |
| Internal Clearance | C0-Medium |
| Adapter Part Number | Not Applicable Inch Not Applicable Millimeter |
| Outer Diameter (mm) | 140 |
| internal clearance: | C0 |
| Minimum Buy Quantity | N/A |
| static load capacity: | 380000 N |
| Calculation factor (e) | 0,33 |
| lubrication hole type: | Lubrication Groove & Hole |
| dynamic load capacity: | 375000 N |
| Harmonized Tariff Code | 84823080 |
| Calculation factor (Y2) | 3 |
| (Oil) Lubrication Speed | 3800 r/min |
| Calculation factor (Y0) | 2 |
| Manufacturer Item Number | 22313EAE4 |
| Number of Rows of Rollers | Double Row |
| (Grease) Lubrication Speed | 3000 r/min |
| operating temperature range: | Maximum of +200 °C |
| Basic static load rating (C0) | 380 kN |
| Basic dynamic load rating (C) | 300 kN |