



Bearing No. PCM 556050 E

| | |
|-------------------------------------|----------------------|
| D | 60 mm |
| d | 55 mm |
| B | 50 mm |
| M | – mm |
| Weight | 0,17 Kg |
| c1 min | 0,2 mm |
| c2 min | 1,2 mm |
| Size (mm) | 55x60x50 |
| Width (mm) | 50 |
| Mass bushing | 0.17 kg |
| ? ±8 | 20 ° |
| Bearing number | PCM 556050 E |
| Tolerance shaft | f7 |
| Tolerance housing | H7 |
| c ₂ min. | 1.2 mm |
| c ₁ min. | 0.2 mm |
| c ₁ max. | 1 mm |
| c ₂ max. | 2.4 mm |
| Bore Diameter (mm) | 55 |
| Outer Diameter (mm) | 60 |
| Basic dynamic load rating (C) | 216 kN |
| Specific dynamic load factor K | 80 N/mm ² |
| Permissible sliding velocity v min. | 0 m/s |
| Permissible sliding velocity v max. | 2 m/s |
| Coefficient of friction μ min. | 0.03 |
| Coefficient of friction μ max. | 0.25 |

| | |
|---|-----------------------|
| Specific static load factor K_0 | 250 N/mm ² |
| Basic dynamic load rating - radial direction C | 216 kN |
| Basic static load rating - radial direction C_0 | 680 kN |
| Factor depending on material and bearing type K_M | 480 |