



Bearing No. BEAM 025075-2RS/PE

J	58 mm
a	84 mm
d	25 mm
D	75 mm
H	6.8 mm
Bore	0.984 Inch   25 Millimeter
Noun	Bearing
Width	1.102 Inch   28 Millimeter
UNSPSC	31171531
Preload	1920 N
Category	Precision Ball Bearings
Enclosure	2 Seals
Inventory	0.0
Size (mm)	25x75x28
Width (mm)	28
Flush Ground	No
Weight / LBS	0.062
Mass bearing	0.72 kg
Product Group	B04270
H <sub>1</sub>	19 mm
Inch - Metric	Metric
Cage Material	Polyamide
D <sub>1</sub>	49 mm
Raceway Style	Not Applicable
Contact Angle	60 Degree
d <sub>1</sub>	40.5 mm
Keyword String	Ball Angular Contact
Other Features	Double Row   Angular

	Contact Thrust Bearing   Double Direction
Enclosure Type	Contact Seal
Bearing number	BEAM 025075-2RS/PE
Limiting speed	3400 r/min
Precision Class	ABEC 5   ISO P5
Material - Ball	Steel
Rolling Element	Ball Bearing
Outside Diameter	2.953 Inch   75 Millimeter
Long Description	25MM Bore; 75MM Outside Diameter; 28MM Width; 2 Seals Enclosure; ABEC 5   ISO P5 Precision; Steel Ball Material; 1 (Single) Bearing; 60 Degree Contact Angle; Polyamide Cage Material; Ball Bearing
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Name	SKF
Frictional moment	0.4 N·m
Weight / Kilogram	0
Bore Diameter (mm)	25
Number of Bearings	1 (Single)
Outer Diameter (mm)	75
$d_a$ - min.	32 mm
$D_a$ - max.	49 mm
Minimum Buy Quantity	N/A
$r_a$ - max.	0.6 mm
Static Axial rigidity	770 N/micron
Harmonized Tariff Code	8482.10.50.28
$r_{3,4}$ - min.	0.8 mm
$r_{1,2}$ - min.	0.3 mm
Manufacturer Item	BEAM 025075-2RS/PE

Number	
Required attachment bolt size	M6
Basic dynamic load rating - C	27.6 kN
Fatigue load limit - $P_u$	2 kN
Basic static load rating - $C_0$	55 kN