



Bearing No. PCM 303425 E

| | |
|-------------------------------------|----------------------|
| D | 34 mm |
| d | 30 mm |
| B | 25 mm |
| M | – mm |
| Weight | 0,037 Kg |
| c1 min | 0,1 mm |
| c2 min | 0,8 mm |
| Size (mm) | 30x34x25 |
| Width (mm) | 25 |
| Mass bushing | 0.037 kg |
| ? ±8 | 20 ° |
| Bearing number | PCM 303425 E |
| Tolerance shaft | f7 |
| Tolerance housing | H7 |
| c ₂ min. | 0.8 mm |
| c ₁ min. | 0.1 mm |
| c ₁ max. | 0.7 mm |
| c ₂ max. | 1.6 mm |
| Bore Diameter (mm) | 30 |
| Outer Diameter (mm) | 34 |
| Basic dynamic load rating (C) | 58,5 kN |
| Specific dynamic load factor K | 80 N/mm ² |
| Permissible sliding velocity v min. | 0 m/s |
| Permissible sliding velocity v max. | 2 m/s |
| Coefficient of friction μ min. | 0.03 |
| Coefficient of friction μ max. | 0.25 |

| | |
|---|-----------------------|
| Specific static load factor K_0 | 250 N/mm ² |
| Basic dynamic load rating - radial direction C | 58.5 kN |
| Basic static load rating - radial direction C_0 | 180 kN |
| Factor depending on material and bearing type K_M | 480 |