



Bearing No. RAK1-3/8

| | |
|----------------|--|
| L | 172,009 mm |
| d | 34,925 mm |
| A | 46,508 mm |
| B | 51,308 mm |
| H | 46 mm |
| J | 129,998 mm |
| N | 15,012 mm |
| N1 | 7,9 mm |
| S1 | 32,512 mm |
| d3 | 51,004 mm |
| A1 | 29,007 mm |
| H1 | 17,399 mm |
| H2 | 92,101 mm |
| Noun | Bearing |
| Bore | 1.375 Inch 34.925 Millimeter |
| Seals | Double Land Riding Rubber Contact |
| UNSPSC | 31171511 |
| Category | Pillow Block |
| Inventory | 0.0 |
| Thread (Q) | 1/8 NPT |
| Weight / LBS | 3.749 |
| Product Group | M06110 |
| Inch - Metric | Inch |
| Housing Style | 2 Bolt Pillow Block |
| Relubricatable | Yes |
| Keyword String | Pillow Block |
| Other Features | Single Row Low Base With Set Screw |
| Bearing number | RAK1-3/8 |

| | |
|---------------------------------|--|
| Mounting Method | Eccentric Collar |
| Rolling Element | Ball Bearing |
| Housing Material | Cast Iron |
| Manufacturer URL | http://www.ina.com |
| Length Thru Bore | 2.012 Inch 51.1 Millimeter |
| Long Description | 2 Bolt Pillow Block; 1-3/8" Bore; 1-13/16" Base to Center Height; Eccentric Collar Mount; Ball Bearing; 4.807" Minimum Bolt Spacing; 5.429" Bolt Spacing Maximum; Relubricatable; Ca |
| Weight / Kilogram | 1.916 |
| Manufacturer Name | SCHAEFFLER GROUP |
| Bore Diameter (mm) | 34,925 |
| Insert Part Number | G1106KRRB |
| Minimum Buy Quantity | N/A |
| Bolt Spacing Minimum | 4.807 Inch 122.1Millimeter |
| Bolt Spacing Maximum | 5.429 Inch 137.9Millimeter |
| Housing Configuration | 1 Piece Solid |
| Base to Center Height | 1.813 Inch 46.05 Millimeter |
| Harmonized Tariff Code | 8483.20.40.40 |
| Manufacturer Item Number | RAK1-3/8 |
| Number of Mounting Holes | 2 |
| Expansion / Non- expansion | Non-expansion |
| Actual Bolt Center to Center | 0 Inch 0Millimeter |
| Nominal Bolt Center to | 5 Inch 127 Millimeter |

| | |
|--------|--|
| Center | |
|--------|--|