



**Bearing No. RASE15/16**

L	139,7 mm
d	23,813 mm
A	37,008 mm
B	44,501 mm
H	36,526 mm
J	104,801 mm
N	11,989 mm
N1	9,5 mm
S1	27,001 mm
d3	37,491 mm
A1	21,997 mm
H1	15,494 mm
H2	71,451 mm
Noun	Bearing
Bore	0.938 Inch   23.825 Millimeter
Seals	Double Land Riding Rubber Contact
UNSPSC	31171511
Category	Pillow Block
Inventory	0.0
Thread (Q)	1/8 NPT
Weight / LBS	1.985
Product Group	M06110
Inch - Metric	Inch
Housing Style	2 Bolt Pillow Block
Relubricatable	Yes
Keyword String	Pillow Block
Other Features	Single Row   Standard Shaft Height   With Set Screw

Bearing number	RASE15/16
Rolling Element	Ball Bearing
Mounting Method	Eccentric Collar
Housing Material	Cast Iron
Long Description	2 Bolt Pillow Block; 15/16" Bore; 1-7/16" Base to Center Height; Eccentric Collar Mount; Ball Bearing; 3.751" Minimum Bolt Spacing; 4-1/2" Bolt Spacing Maximum; Relubricatable; Cas
Manufacturer URL	<a href="http://www.ina.com">http://www.ina.com</a>
Length Thru Bore	1.748 Inch   44.4 Millimeter
Weight / Kilogram	0.9
Manufacturer Name	SCHAEFFLER GROUP
Bore Diameter (mm)	23,813
Insert Part Number	G1015KRRB
Minimum Buy Quantity	N/A
Bolt Spacing Maximum	4.5 Inch   114.3Millimeter
Bolt Spacing Minimum	3.751 Inch   95.275Millimeter
Base to Center Height	1.438 Inch   36.525 Millimeter
Housing Configuration	1 Piece Solid
Harmonized Tariff Code	8483.20.40.40
Manufacturer Item Number	RASE15/16
Number of Mounting Holes	2
Expansion / Non- expansion	Non-expansion
Actual Bolt Center to Center	0 Inch   0Millimeter

Nominal Bolt Center to Center	4.1 Inch   105 Millimeter
-------------------------------	---------------------------