




Bearing No. 1206

D	62 mm
d	30 mm
B	16 mm
C	16 mm
Noun	Bearing
Bore	1.181 Inch 30 Millimeter
Weight	0.220 Kg
UNSPSC	31171532
Da max.	47 mm
ra max.	1.0 mm
r1 min.	1 mm
da min.	35 mm
Category	Self Aligning Ball Bearings
Enclosure	Open
Size (mm)	30x62x16
Inventory	0.0
Width (mm)	16
Weight / LBS	0.48502
Product Group	B00152
Cage Material	Steel
Inch - Metric	Metric
Keyword String	Self Aligning
Other Features	Allowable Misalignment 2.5 Deg
Bearing number	1206
Precision Class	ABEC 1 ISO P0
Mounting Method	Shaft
Rolling Element	Ball Bearing
Manufacturer URL	http://www.nachi.com

Long Description	30MM Bore; Shaft Mount; 62MM Outside Diameter; 16MM Inner Race Width; 16MM Outer Race Width; Open; Steel Cage; Double Row of Balls; ABEC 1 ISO P0; C0-Medium
Outside Diameter	2.441 Inch 62 Millimeter
Outer Race Width	0.63 Inch 16 Millimeter
Inner Race Width	0.63 Inch 16 Millimeter
Manufacturer Name	NACHI
Weight / Kilogram	0
Internal Clearance	C0-Medium
Bore Diameter (mm)	30
Outer Diameter (mm)	62
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Calculation factor (e)	0.25
Number of Rows of Balls	Double Row
Calculation factor (Y1)	2.55
Calculation factor (Y0)	2.67
(Oil) Lubrication Speed	12000 r/min
(Grease) Lubrication Speed	10000 r/min
Basic static load rating (C0)	4,65 kN
Basic dynamic load rating (C)	15,6 kN