



Bearing No. 52209

| | |
|----------------|----------------------------|
| B | 9 mm |
| d | 45 mm |
| D | 73 mm |
| T | 37 mm |
| d2 | 35 mm |
| T2 | 23 mm |
| d3 | 73 mm |
| D1 | 47 mm |
| Noun | Bearing |
| Weight | 0,606 Kg |
| Bore 2 | 1.85 Inch 47 Millimeter |
| Height | 1.457 Inch 37 Millimeter |
| UNSPSC | 31171552 |
| r min. | 1 mm |
| Banded | No |
| Bore 1 | 1.378 Inch 35 Millimeter |
| rb max. | 0,6 mm |
| ra max. | 1 mm |
| Da max. | 60 mm |
| r1 min. | 0,6 mm |
| Category | Thrust Ball Bearings |
| Inventory | 0.0 |
| Size (mm) | 45x73x37 |
| Width (mm) | 37 |
| Weight / LBS | 1.336 |
| Cage Material | Steel |
| Inch - Metric | Metric |
| Product Group | B00308 |
| Thrust Bearing | Yes |

| | |
|-------------------------------------|---|
| Keyword String | Ball Thrust |
| Other Features | Double Row With Flat Seat |
| Bearing number | 52209 |
| Rolling Element | Ball Bearing |
| Precision Class | Non-Precision |
| Manufacturer URL | http://www.nskamericas.com |
| Outside Diameter | 2.874 Inch 73 Millimeter |
| Long Description | 35MM Bore 1; 47MM Bore 2; 73MM Outside Diameter; 37MM Height; Ball Bearing; Double Direction; Not Banded; Steel Cage; Non-Precision |
| Weight / Kilogram | 0.62 |
| Manufacturer Name | NSK |
| Bore Diameter (mm) | 45 |
| Outer Diameter (mm) | 73 |
| Minimum Buy Quantity | N/A |
| Component Description | Roller Assembly Plus Raceways |
| Harmonized Tariff Code | 8482.10.50.08 |
| Manufacturer Item Number | 52209 |
| Single or Double Direction | Double Direction |
| (Grease) Lubrication Speed | 2400 r/min |
| Basic static load rating (C0) | 105 kN |
| Basic dynamic load rating (C) | 48 kN |
| Overall Height with Aligning Washer | 0 Inch 0 Millimeter |

