



Bearing No. RASE20-N

N	11 mm
d	20 mm
A	32 mm
H	33,3 mm
J	97 mm
L	130 mm
N1	19 mm
S1	26,6 mm
d3	33 mm
A1	19 mm
B1	43,7 mm
H1	14,5 mm
H2	64 mm
Noun	Bearing
Bore	0.787 Inch 20 Millimeter
Seals	Double Land Riding Rubber Contact
UNSPSC	31171511
Weight	0,63 Kg
Category	Pillow Block
Inventory	0.0
Thread (Q)	Rp1/8
Weight / LBS	1.323
Product Group	M06110
Housing Style	2 Bolt Pillow Block
Inch - Metric	Metric
Relubricatable	Yes
Keyword String	Pillow Block
Other Features	Single Row Standard Shaft Height With Set

	Screw
Bearing number	RASE20-N
Mounting Method	Eccentric Collar
Rolling Element	Ball Bearing
Manufacturer URL	http://www.ina.com
Housing Material	Cast Iron
Length Thru Bore	1.72 Inch 43.7 Millimeter
Long Description	2 Bolt Pillow Block; 20MM Bore; 33.3MM Base to Center Height; Eccentric Collar Mount; Ball Bearing; 87MM Minimum Bolt Spacing; 105MM Bolt Spacing Maximum; Relubricatable; Cast Iron; Double Land Riding
Manufacturer Name	SCHAEFFLER GROUP
Weight / Kilogram	0.742
Bore Diameter (mm)	20
Insert Part Number	GE20KRRB
Bolt Spacing Maximum	4.134 Inch 105Millimeter
Bolt Spacing Minimum	3.425 Inch 87Millimeter
Minimum Buy Quantity	N/A
Housing Configuration	1 Piece Solid
Base to Center Height	1.311 Inch 33.3 Millimeter
Harmonized Tariff Code	8483.20.40.40
Manufacturer Item Number	RASE20N
Number of Mounting Holes	2
Expansion / Non- expansion	Non-expansion



Actual Bolt Center to Center	0 Inch 0Millimeter
Basic dynamic load rating (C)	12,8 kN
Nominal Bolt Center to Center	3.8 Inch 97 Millimeter