



Bearing No. RNA5924

| | |
|------------|--------------|
| D | 165 mm |
| r | 1.1 |
| C | 60 mm |
| d | 135 |
| SI | 0 |
| D_ | 165 |
| Fw | 135 mm |
| C0 | 565 |
| ra | 1 |
| Z_ | 30 |
| B_ | 60 |
| SLR | 50 |
| DE_ | 154 |
| C1_ | 60 |
| DA_ | 9.5 |
| SDM_ | 144.5 |
| yobi | RNA5924 |
| KBRG | 8313 |
| mass1 | 2.7 |
| LangID | 1 |
| da_max | 158 |
| Weight | 2,7 Kg |
| r min. | 1,1 mm |
| hidYobi | RNA5924 |
| GRS rpm | 1900 |
| OIL rpm | 3000 |
| hidTable | ecat_NS MRNR |
| Size (mm) | 135x165x60 |
| Prod_Type3 | NRB_S_RNA |
| Width (mm) | 60 |

| | |
|-------------------------------|------------|
| Bearing number | RNA5924 |
| Bore Diameter (mm) | 135 |
| Outer Diameter (mm) | 165 |
| (Oil) Lubrication Speed | 3000 r/min |
| (Grease) Lubrication Speed | 1900 r/min |
| Basic static load rating (C0) | 565 kN |
| Basic dynamic load rating (C) | 253 kN |