



Bearing No. PCM 101210 M

| | |
|-------------------------------------|-----------------------|
| D | 12 mm |
| d | 10 mm |
| B | 10 mm |
| M | 3 mm |
| Weight | 0,0019 Kg |
| c1 min | 0,1 mm |
| c2 min | 0,2 mm |
| Size (mm) | 10x12x10 |
| Width (mm) | 10 |
| Mass bushing | 0.0019 kg |
| ? ±8 | 20 ° |
| Bearing number | PCM 101210 M |
| Tolerance shaft | h8 |
| Tolerance housing | H7 |
| c ₂ min. | 0.2 mm |
| c ₁ min. | 0.1 mm |
| c ₁ max. | 0.6 mm |
| c ₂ max. | 1 mm |
| Bore Diameter (mm) | 10 |
| Outer Diameter (mm) | 12 |
| Basic dynamic load rating (C) | 12 kN |
| Specific dynamic load factor K | 120 N/mm ² |
| Permissible sliding velocity v min. | 0 m/s |
| Permissible sliding velocity v max. | 2.5 m/s |
| Coefficient of friction μ min. | 0.02 |
| Coefficient of friction μ max. | 0.2 |

| | |
|---|-----------------------|
| Specific static load factor K_0 | 250 N/mm ² |
| Basic dynamic load rating - radial direction C | 12 kN |
| Basic static load rating - radial direction C_0 | 25 kN |
| Factor depending on material and bearing type K_M | 1900 |