



Bearing No. L623149/L623110

e	0.41
d	114,3 mm
D	152,4 mm
T	21,433 mm
B	21,433 mm
C	16,67 mm
a	27,4 mm
Da	143 mm
B_	21.433
Db	148 mm
da	123 mm
Y0	0.8
db	121 mm
C0	178
D_	152.4
Z_	42
C_	16.67
Y1	1.5
DE_	140.872
SLR	15.5
D_a	143
DI_	126.449
DA1	7.533
DA2	7.106
CUP	0.344
DA_	7.32
D_b	148
RAr	272.617
SDM_	133.604
KBRG	3161

yobi	L623149/L623110
CONE	0.725
ALP21	30
ALP22	48
ALP23	0
BETA_	0
BET21	1
BET23	0
BET22	35
r min.	1,5 mm
LangID	1
Weight	1,069 Kg
ALPHA_	15.4
r1 min.	1,5 mm
ra max.	1,5 mm
Oil rpm	2800
outer r	1.5
hidYobi	L623149/L623110
GRS rpm	2000
inner r	1.5
hidTable	ecat_NSTPRI
inner ra	1.5
outer rb	1.5
ra1 max.	1,5 mm
Size (mm)	114.3x152.4x21.433
SHOG_yobi	L623149R/L623110R
Prod_Type3	TRBSR_ID_A
Width (mm)	21,433
Bearing number	L623149/L623110
Bore Diameter (mm)	114,3
Outer Diameter (mm)	152,4
Calculation factor (e)	0,41

(Oil) Lubrication Speed	2800 r/min
Calculation factor (Y0)	0,8
(Grease) Lubrication Speed	2000 r/min
Basic static load rating (C0)	178 kN
Basic dynamic load rating (C)	89,5 kN