



Bearing No. 26882/26820

e	0.32
d	41,275 mm
D	80,167 mm
T	25,4 mm
B	25,4 mm
C	20,638 mm
a	18 mm
Da	69 mm
B_	25.4
Db	74 mm
da	54 mm
Y0	1
db	47 mm
C0	98.5
D_	80.167
Z_	18
C_	20.638
Y1	1.9
DE_	68.237
SLR	18
D_a	69
DI_	51.173
DA1	9.237
DA2	8.283
CUP	0.219
DA_	8.762
D_b	74
RAr	173.558
SDM_	59.835
KBRG	3161

yobi	26882/26820
CONE	0.349
ALP21	24
ALP22	0
ALP23	0
BETA_	1
BET21	3
BET23	0
BET22	3
r min.	3,5 mm
LangID	1
Weight	0,568 Kg
ALPHA_	12
r1 min.	3,3 mm
ra max.	3,5 mm
Oil rpm	6300
outer r	3.3
hidYobi	26882/26820
GRS rpm	4800
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	3.3
ra1 max.	3,3 mm
Size (mm)	41.275x80.167x25.4
SHOG_yobi	26882/26820
Prod_Type3	TRBSR_ID_A
Width (mm)	25,4
Bearing number	26882/26820
Bore Diameter (mm)	41,275
Outer Diameter (mm)	80,167
Calculation factor (e)	0,32

(Oil) Lubrication Speed	6300 r/min
Calculation factor (Y0)	1
(Grease) Lubrication Speed	4800 r/min
Basic static load rating (C0)	98,5 kN
Basic dynamic load rating (C)	77 kN