



Bearing No. 60/32

r	1
d	32 mm
D	58 mm
B	13 mm
C	13 mm
fo	14.5
C0	9.15
B_	13
Z_	10
ra	1
D_	58
SRI	4.01
DA_	7.938
SRE	4.21
DE_	52.938
DI_	37.062
D_a	53
SREN	0
Bore	1.26 Inch 32 Millimeter
SRIN	0
mass	0.122
bomp	0
Noun	Bearing
yobi	60/32
SRIX	0.02
SDM_	45
SREX	0.04
KBRG	6101
SBRG	10
C_conv	15100

ALPHA_	0
Weight	0,122 Kg
da max	38,5 mm
r min.	1 mm
da min	37
UNSPSC	31171504
LangID	1
hidYobi	60/32
GRS rpm	12000
Oil rpm	14000
Da max.	53 mm
ra max.	1 mm
da min.	37 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	32x58x13
Snap Ring	No
Enclosure	Open
Inventory	0.0
Width (mm)	13
Prod_Type3	DGBB_SR_OT
Weight / LBS	0.269
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Bearing number	60/32
Keyword String	Ball
Other Features	Deep Groove
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Outside Diameter	2.283 Inch 58 Millimeter
Long Description	32MM Bore; 58MM

	Outside Diameter; 13MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Outer Race Width	0.512 Inch 13 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Manufacturer URL	http://www.nskamericas.com
Manufacturer Name	NSK
Weight / Kilogram	0.121
Internal Clearance	C0-Medium
Bore Diameter (mm)	32
Outer Diameter (mm)	58
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	14 000 r/min
Internal Special Features	No
(Grease) Lubrication Speed	12 000 r/min
Basic static load rating (C0)	9,15 kN
Basic dynamic load rating (C)	15,1 kN
Maximum Capacity / Filling Slot	No