



Bearing No. 60/32

D	58 mm
d	32 mm
B	13 mm
C	13 mm
f0	15.4
Noun	Bearing
Bore	1.26 Inch 32 Millimeter
Mass	0.13 kg
Weight	0,129 Kg
Da max	53 mm
rs min	1 mm
UNSPSC	31171504
da min	37 mm
ra max	1 mm
r min.	1 mm
da max	39 mm
da min.	37 mm
Da max.	53 mm
ra max.	1 mm
Category	Single Row Ball Bearing
Enclosure	Open
Inventory	5.0
Size (mm)	32x58x13
Snap Ring	No
Width (mm)	13
Nlim (oil)	15,000 rpm
Weight / LBS	0.295
Inch - Metric	Metric
Cage Material	Steel
Nlim (grease)	12,000 rpm

Product Group	B00308
Other Features	Deep Groove
Keyword String	Ball
Bearing number	60/32
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Static load, C0	8.05 kN
Dynamic load, C	11.8 kN
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.512 Inch 13 Millimeter
Outside Diameter	2.283 Inch 58 Millimeter
Long Description	32MM Bore; 58MM Outside Diameter; 13MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Manufacturer URL	http://www.ntnamerica.com
Weight / Kilogram	0.134
Manufacturer Name	NTN
Bore Diameter (mm)	32
Internal Clearance	C0-Medium
Outer Diameter (mm)	58
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Radial clearance class	CN
Fatigue limit load, Cu	0.37 kN
(Oil) Lubrication Speed	15 000 r/min
Manufacturer Item	60/32

Number	
Internal Special Features	No
(Grease) Lubrication Speed	12 000 r/min
Basic static load rating (C0)	8,05 kN
Basic dynamic load rating (C)	11,8 kN
Maximum Capacity / Filling Slot	No
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C