




Bearing No. 60/32ZZ

D	58 mm
d	32 mm
B	13 mm
C	13 mm
r	1
Z_	10
B_	13
D_	58
ra	1
C0	9.15
fo	14.5
DI_	37.062
SRI	4.01
D_a	53
DE_	52.938
DA_	7.938
SRE	4.21
SRIN	0
SBRG	10
yobi	60/32ZZ
SDM_	45
SREX	0.04
KBRG	6141
bomp	0
mass	0.122
Bore	1.26 Inch 32 Millimeter
SRIX	0.02
SREN	0
Noun	Bearing
ALPHA_	0

da min	37
LangID	1
r min.	1 mm
UNSPSC	31171504
C_conv	15100
da max	38,5 mm
Weight	0,122 Kg
hidYobi	60/32ZZ
Da max.	53 mm
da min.	37 mm
ra max.	1 mm
GRS rpm	12000
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Inventory	0.0
Enclosure	2 Metal Shields
Snap Ring	No
Size (mm)	32x58x13
Width (mm)	13
Prod_Type3	DGBB_SR_ZZ
Weight / LBS	0.269
Cage Material	Steel
Product Group	B00308
Inch - Metric	Metric
Bearing number	60/32ZZ
Keyword String	Ball
Other Features	Deep Groove
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	2.283 Inch 58 Millimeter
Long Description	32MM Bore; 58MM

	Outside Diameter; 13MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stee
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	0.512 Inch 13 Millimeter
Weight / Kilogram	0.121
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	32
Outer Diameter (mm)	58
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
(Grease) Lubrication Speed	12 000 r/min
Basic static load rating (C0)	9,15 kN
Basic dynamic load rating (C)	15,1 kN
Maximum Capacity / Filling Slot	No