



Bearing No. 26882/26822

e	0.32
d	41,275 mm
D	79,375 mm
T	23,812 mm
B	25,4 mm
C	19,05 mm
a	16,4 mm
Da	71 mm
B_	25.4
Db	74 mm
da	54 mm
Y0	1
db	47 mm
C0	98.5
D_	79.375
Z_	18
C_	19.05
Y1	1.9
DE_	68.574
SLR	18
D_a	71
DI_	51.173
DA1	9.237
DA2	8.283
CUP	0.186
DA_	8.762
D_b	74
RAr	173.558
SDM_	59.835
KBRG	3161

yobi	26882/26822
CONE	0.349
ALP21	24
ALP22	0
ALP23	0
BETA_	1
BET21	3
BET23	0
BET22	3
r min.	3,5 mm
LangID	1
Weight	0,535 Kg
ALPHA_	12
r1 min.	0,8 mm
ra max.	3,5 mm
Oil rpm	6300
outer r	0.8
hidYobi	26882/26822
GRS rpm	4800
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	0.8
ra1 max.	0,8 mm
Size (mm)	41.275x79.375x23.812
SHOG_yobi	26882/26822
Prod_Type3	TRBSR_ID_A
Width (mm)	23,812
Bearing number	26882/26822
Bore Diameter (mm)	41,275
Outer Diameter (mm)	79,375
Calculation factor (e)	0,32

(Oil) Lubrication Speed	6300 r/min
Calculation factor (Y0)	1
(Grease) Lubrication Speed	4800 r/min
Basic static load rating (C0)	98,5 kN
Basic dynamic load rating (C)	77 kN