



Bearing No. 26884/26823

e	0.32
d	42,875 mm
D	76,2 mm
T	25,4 mm
B	25,4 mm
C	20,638 mm
a	18 mm
Da	69 mm
B_	25.4
Db	73 mm
da	55 mm
Y0	1
db	48,5 mm
C0	98.5
D_	76.2
Z_	18
C_	20.638
Y1	1.9
DE_	68.237
SLR	18
D_a	69
DI_	51.173
DA1	9.237
DA2	8.283
CUP	0.136
DA_	8.762
D_b	73
RAr	173.558
SDM_	59.835
KBRG	3161

yobi	26884/26823
CONE	0.337
ALP21	24
ALP22	0
ALP23	0
BETA_	1
BET21	3
BET23	0
BET22	3
r min.	3,5 mm
LangID	1
Weight	0,473 Kg
ALPHA_	12
r1 min.	1,5 mm
ra max.	3,5 mm
Oil rpm	6300
outer r	1.5
hidYobi	26884/26823
GRS rpm	4800
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	1.5
ra1 max.	1,5 mm
Size (mm)	42.875x76.2x25.4
SHOG_yobi	26884R/26823R
Prod_Type3	TRBSR_ID_A
Width (mm)	25,4
Bearing number	26884/26823
Bore Diameter (mm)	42,875
Outer Diameter (mm)	76,2
Calculation factor (e)	0,32

(Oil) Lubrication Speed	6300 r/min
Calculation factor (Y0)	1
(Grease) Lubrication Speed	4800 r/min
Basic static load rating (C0)	98,5 kN
Basic dynamic load rating (C)	77 kN