



Bearing No. RCJT75

J	216 mm
N	21 mm
d	75 mm
V	160 mm
U	83,6 mm
A	57 mm
H	258 mm
L	160 mm
d3	100 mm
A1	18 mm
B1	67 mm
A2	38 mm
Noun	Bearing
Bore	2.953 Inch 75 Millimeter
Seals	Double Land Riding Rubber Contact
Weight	6 Kg
UNSPSC	31171501
Category	Flange Block
Inventory	0.0
Thread (Q)	Rp1/8
Bolt Spacing	8.504 Inch 216 Millimeter
Weight / LBS	13.23
Inch - Metric	Metric
Housing Style	2 Bolt Flange Block
Product Group	M06110
Bearing number	RCJT75
Relubricatable	Yes
Keyword String	Flanged

Other Features	Single Row With Set Screw
Mounting Bolts	21 Millimeter
Rolling Element	Ball Bearing
Mounting Method	Eccentric Collar
Manufacturer URL	http://www.ina.com
Housing Material	Cast Iron
Long Description	2 Bolt Flange Block; 75MM Bore; 215MM Bolt Circle; 216MM Bolt Spacing; 1 Piece Solid; Eccentric Collar Mount; Cast Iron; Ball Bearing; 67.1MM Length Thru Bore; Relubricatable; Double Land Riding Rubbe
Length Thru Bore	2.642 Inch 67.1 Millimeter
Weight / Kilogram	7.047
Manufacturer Name	SCHAEFFLER GROUP
Insert Part Number	GE75KRRB
Bore Diameter (mm)	75
Pilot Configuration	No Pilot
Minimum Buy Quantity	N/A
Cartridge Pilot Depth	0 Inch 0 Millimeter
Housing Configuration	1 Piece Solid
Harmonized Tariff Code	8483.20.40.40
Manufacturer Item Number	RCJT75
Cartridge Pilot Diameter	0 Inch 0 Millimeter
Number of Mounting Holes	2
Expansion / Non-expansion	Non-expansion
Basic dynamic load rating (C)	62 kN

Nominal Bolt Circle Diameter Round	8.5 Inch 215 Millimeter
---------------------------------------	---------------------------