



Bearing No. C 30/950 KMB + AOH 30/950

D	1360 mm
G	Tr 1000x8
B	300 mm
Size (mm)	1360x900x355
Width (mm)	355
G <sub>1</sub>	1000 mm
s <sub>1</sub>	37.8 mm
d <sub>1</sub>	900 mm
B <sub>1</sub>	355 mm
d <sub>2</sub>	1075 mm
D <sub>1</sub>	1241 mm
Bearing number	C 30/950 KMB + AOH 30/950
Limiting speed	380 r/min
Reference speed	280 r/min
Bore Diameter (mm)	1360
Outer Diameter (mm)	900
d <sub>a</sub> - min.	978 mm
d <sub>a</sub> - max.	1073 mm
D <sub>a</sub> - min.	1204 mm
D <sub>a</sub> - max.	1332 mm
C <sub>a</sub> - min.	8.7 mm
r <sub>a</sub> - max.	6 mm
Factor - k <sub>1</sub>	
r <sub>1,2</sub> - min.	7.5 mm
Factor - k <sub>2</sub>	0.107
Basic dynamic load rating - C	13200 kN
Fatigue load limit - P <sub>u</sub>	1600 kN

Basic static load rating - $C_0$	28500 kN
-------------------------------------	----------