



Bearing No. 6000

r	0.3
d	10 mm
D	26 mm
B	8 mm
C	8 mm
fo	12.4
D_	26
B_	8
ra	0.3
Z_	7
C0	1.97
DI_	13.238
SRE	2.67
D_a	24
DE_	22.762
SRI	2.46
DA_	4.762
SREN	-0.015
Noun	Bearing
SRIN	-0.015
bomp	0
SRIX	0.015
yobi	6000
mass	0.018
SDM_	18
KBRG	6101
SREX	0.015
SBRG	10
Bore	0.394 Inch 10 Millimeter

LangID	1
Weight	0,018 Kg
r min.	0,3 mm
ALPHA_	0
C_conv	4550
da min	12
UNSPSC	31171504
da max	13 mm
Oil rpm	36000
GRS rpm	30000
ra max.	0,3 mm
hidYobi	6000
Da max.	24 mm
da min.	12 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Inventory	0.0
Snap Ring	No
Enclosure	Open
Size (mm)	10x26x8
Prod_Type3	DGBB_SR_OT
bore type:	Round
Width (mm)	8
Weight / LBS	0.019
Inch - Metric	Metric
closure type:	Open
Product Group	B00308
Cage Material	Steel
Keyword String	Ball
overall width:	8 mm
Bearing number	6000
bore diameter:	10 mm

Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	1.024 Inch 26 Millimeter
Long Description	10MM Bore; 26MM Outside Diameter; 8MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	0.315 Inch 8 Millimeter
Weight / Kilogram	0.01
Manufacturer Name	NSK
outside diameter:	26 mm
Internal Clearance	C0-Medium
Bore Diameter (mm)	10
Outer Diameter (mm)	26
internal clearance:	Normal Clearance
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	36 000 r/min
manufacturer upc number:	029176012167
Manufacturer Item Number	6000
Internal Special Features	No
(Grease) Lubrication Speed	30 000 r/min
Basic dynamic load rating (C)	4,55 kN
Basic static load rating (C0)	1,97 kN

Maximum Capacity / Filling Slot	No
------------------------------------	----