



**Bearing No. 2777/2720**

|                                  |                  |
|----------------------------------|------------------|
| C                                | 19,05 mm         |
| R                                | 5,6 mm           |
| d                                | 38,1 mm          |
| D                                | 76,2 mm          |
| T                                | 23,774 mm        |
| B                                | 25,654 mm        |
| r                                | 3,3 mm           |
| Db                               | 66 mm            |
| da                               | 43,5 mm          |
| db                               | 54 mm            |
| Da                               | 70 mm            |
| a -                              | 8,1 mm           |
| Weight                           | 0,49 Kg          |
| Size (mm)                        | 38.1x76.2x23.774 |
| Width (mm)                       | 23,774           |
| Factor (K)                       | 1,93             |
| Factor (G1)                      | 28,7             |
| Factor (Cg)                      | 0,0177           |
| Factor (G2)                      | 12,2             |
| Bearing number                   | 2777/2720        |
| Bore Diameter (mm)               | 38,1             |
| Outer Diameter (mm)              | 76,2             |
| Calculation factor (e)           | 0,3              |
| Basic static load rating (C0)    | 102 kN           |
| Basic dynamic load rating (C1)   | 80,4 kN          |
| Basic dynamic load rating (C90)  | 20,8             |
| Basic dynamic load rating (Ca90) | 10,8             |

