



Bearing No. 6000-RSH

D	26 mm
d	10 mm
B	8 mm
C	8 mm
d1	- mm
d2	13 mm
D1	22,6 mm
D2	0,3 mm
Bore	0.394 Inch 10 Millimeter
Noun	Bearing
UNSPSC	31171504
Weight	0,019 Kg
da min.	12,5 mm
Da max.	24 mm
ra max.	0,3 mm
r1 min.	12 mm
r2 min.	12 mm
Category	Single Row Ball Bearing
Enclosure	1 Seal
Snap Ring	No
Size (mm)	10x26x8
Inventory	0.0
Width (mm)	8
Mass bearing	0.019 kg
Weight / LBS	0.0438
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Enclosure Type	Contact Seal

Other Features	Deep Groove NBR Seal
Keyword String	Ball
Bearing number	6000-RSH
Limiting speed	19000 r/min
Reference speed	– r/min
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Long Description	10MM Bore; 26MM Outside Diameter; 8MM Outer Race Width; 1 Seal; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage; Co
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.315 Inch 8 Millimeter
Manufacturer URL	http://www.skf.com
Outside Diameter	1.024 Inch 26 Millimeter
Manufacturer Name	SKF
Weight / Kilogram	0.018
r _a max.	0.3 mm
D _a max.	24 mm
d _a max.	12.5 mm
Internal Clearance	C0-Medium
d _a min.	12 mm
Bore Diameter (mm)	10
Outer Diameter (mm)	26
r _{1,2} min.	0.3 mm
Minimum Buy Quantity	N/A
d ₂ ?	12.55 mm

D ₂ ?	22.6 mm
Harmonized Tariff Code	8482.10.50.68
Calculation factor (f ₀)	12
Fatigue load limit (P _u)	0,083
Manufacturer Item Number	6000-RSH
Internal Special Features	No
Basic dynamic load rating C	4.75 kN
Basic dynamic load rating (C)	4,75 kN
Basic static load rating (C ₀)	1,96 kN
Maximum Capacity / Filling Slot	No
Fatigue load limit P _u	0.083 kN
Calculation factor k _r	0.025
Calculation factor f ₀	12
Basic static load rating C ₀	1.96 kN