



Bearing No. RCJTZ20

J	90 mm
d	20 mm
V	60,5 mm
U	45,6 mm
N	11,5 mm
L	60,5 mm
Z	55 mm
H	112,5 mm
A	31,7 mm
B1	43,7 mm
A2	19 mm
A1	10 mm
d3	33 mm
T1	3,5 mm
Bore	0.787 Inch 20 Millimeter
Noun	Bearing
Seals	Double Land Riding Rubber Contact
Weight	0,53 Kg
UNSPSC	31171501
Category	Flange Block
Inventory	2.0
Thread (Q)	Rp1/8
Bolt Spacing	3.543 Inch 90 Millimeter
Weight / LBS	1.169
Housing Style	2 Bolt Flange Block
Inch - Metric	Metric
Product Group	M06110
Bearing number	RCJTZ20

Other Features	Single Row Centering Spigot With Set Screw
Keyword String	Flanged
Relubricatable	Yes
Mounting Bolts	11.5 Millimeter
Mounting Method	Eccentric Collar
Rolling Element	Ball Bearing
Length Thru Bore	1.72 Inch 43.7 Millimeter
Manufacturer URL	http://www.ina.com
Housing Material	Cast Iron
Long Description	2 Bolt Flange Block; 20MM Bore; 90MM Bolt Circle; 90MM Bolt Spacing; 1 Piece Solid; Eccentric Collar Mount; Cast Iron; Ball Bearing; 43.7MM Length Thru Bore; Relubricatable; Double Land Riding Rubber
Manufacturer Name	SCHAEFFLER GROUP
Weight / Kilogram	0.659
Insert Part Number	GE20KRRB
Bore Diameter (mm)	20
Pilot Configuration	With Pilot
Minimum Buy Quantity	N/A
Housing Configuration	1 Piece Solid
Cartridge Pilot Depth	0.138 Inch 3.5 Millimeter
Harmonized Tariff Code	8483.20.40.40
Number of Mounting Holes	2
Manufacturer Item Number	RCJTZ20
Cartridge Pilot Diameter	2.165 Inch 55 Millimeter

Expansion / Non-expansion	Non-expansion
Basic dynamic load rating (C)	12,8 kN
Nominal Bolt Circle Diameter Round	3.5 Inch 90 Millimeter