



Bearing No. RCJTZ30

N	11,5 mm
d	30 mm
V	83 mm
U	47,1 mm
Z	80 mm
A	26 mm
H	142 mm
J	116,5 mm
L	83 mm
A2	17 mm
T1	3 mm
d3	44 mm
A1	12 mm
B1	48,5 mm
Noun	Bearing
Bore	1.181 Inch 30 Millimeter
Seals	Double Land Riding Rubber Contact
UNSPSC	31171501
Weight	0,9 Kg
Category	Flange Block
Inventory	0.0
Thread (Q)	Rp1/8
Weight / LBS	1.985
Bolt Spacing	4.587 Inch 116.5 Millimeter
Product Group	M06110
Housing Style	2 Bolt Flange Block
Inch - Metric	Metric
Relubricatable	Yes

Keyword String	Flanged
Other Features	Single Row Centering Spigot With Set Screw
Bearing number	RCJTZ30
Mounting Bolts	11.5 Millimeter
Rolling Element	Ball Bearing
Mounting Method	Eccentric Collar
Housing Material	Cast Iron
Manufacturer URL	http://www.ina.com
Length Thru Bore	1.906 Inch 48.42 Millimeter
Long Description	2 Bolt Flange Block; 30MM Bore; 117MM Bolt Circle; 116.5MM Bolt Spacing; 1 Piece Solid; Eccentric Collar Mount; Cast Iron; Ball Bearing; 48.42MM Length Thru Bore; Relubricatable; Double Land Riding Ru
Manufacturer Name	SCHAEFFLER GROUP
Weight / Kilogram	0
Insert Part Number	GE30KRRB
Bore Diameter (mm)	30
Pilot Configuration	With Pilot
Minimum Buy Quantity	N/A
Housing Configuration	1 Piece Solid
Cartridge Pilot Depth	0.118 Inch 3 Millimeter
Harmonized Tariff Code	8483.20.40.40
Number of Mounting Holes	2
Manufacturer Item Number	RCJTZ30
Cartridge Pilot Diameter	3.15 Inch 80 Millimeter
Expansion / Non-	Non-expansion

expansion	
Basic dynamic load rating (C)	19,5 kN
Nominal Bolt Circle Diameter Round	4.6 Inch 117 Millimeter