



Bearing No. RCJTZ60

J	202 mm
d	60 mm
V	138 mm
U	76,8 mm
N	18 mm
L	138 mm
Z	130 mm
H	238 mm
A	42 mm
B1	77,9 mm
A2	30 mm
A1	16 mm
d3	84 mm
T1	4 mm
Bore	2.362 Inch 60 Millimeter
Noun	Bearing
Seals	Double Land Riding Rubber Contact
Weight	3,74 Kg
UNSPSC	31171501
Category	Flange Block
Inventory	0.0
Thread (Q)	Rp1/8
Bolt Spacing	7.953 Inch 202 Millimeter
Weight / LBS	8.245
Housing Style	2 Bolt Flange Block
Inch - Metric	Metric
Product Group	M06110
Bearing number	RCJTZ60

Other Features	Single Row Centering Spigot With Set Screw
Keyword String	Flanged
Relubricatable	Yes
Mounting Bolts	18 Millimeter
Mounting Method	Eccentric Collar
Rolling Element	Ball Bearing
Manufacturer URL	http://www.ina.com
Length Thru Bore	3.067 Inch 77.9 Millimeter
Housing Material	Cast Iron
Long Description	2 Bolt Flange Block; 60MM Bore; 202MM Bolt Circle; 202MM Bolt Spacing; 1 Piece Solid; Eccentric Collar Mount; Cast Iron; Ball Bearing; 77.9MM Length Thru Bore; Relubricatable; Double Land Riding Rubbe
Weight / Kilogram	5.005
Manufacturer Name	SCHAEFFLER GROUP
Insert Part Number	GE60KRRB
Bore Diameter (mm)	60
Pilot Configuration	With Pilot
Minimum Buy Quantity	N/A
Housing Configuration	1 Piece Solid
Cartridge Pilot Depth	0.157 Inch 4 Millimeter
Harmonized Tariff Code	8483.20.40.40
Number of Mounting Holes	2
Manufacturer Item Number	RCJTZ60
Cartridge Pilot Diameter	5.118 Inch 130 Millimeter

Expansion / Non-expansion	Non-expansion
Basic dynamic load rating (C)	52 kN
Nominal Bolt Circle Diameter Round	8 Inch 202 Millimeter