



Bearing No. 6000DDU

r	0.3
d	10 mm
D	26 mm
B	8 mm
C	8 mm
D_	26
C0	1.97
Z_	7
ra	0.3
fo	12.4
B_	8
DI_	13.238
SRI	2.46
DE_	22.762
SRE	2.67
DA_	4.762
D_a	24
KBRG	6161
SBRG	10
SRIN	-0.015
bomp	0
SREX	0.015
yobi	6000DDU
SRIX	0.015
mass	0.018
SDM_	18
SREN	-0.015
Bore	0.394 Inch 10 Millimeter
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	12
r min.	0,3 mm
Weight	0,018 Kg
ALPHA_	0
C_conv	4550
da max	13 mm
GRS rpm	22000
Da max.	24 mm
ra max.	0,3 mm
da min.	12 mm
hidYobi	6000DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	10x26x8
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	8
Prod_Type3	DGBB_SR_DD
Weight / LBS	0.0397
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6000DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Inner Race Width	0 Inch 0 Millimeter

Outside Diameter	1.024 Inch 26 Millimeter
Long Description	10MM Bore; 26MM Outside Diameter; 8MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage; C
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	0.315 Inch 8 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	0.019
Internal Clearance	C0-Medium
Bore Diameter (mm)	10
Outer Diameter (mm)	26
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6000DDU
Internal Special Features	No
(Grease) Lubrication Speed	22 000 r/min
Basic static load rating (C0)	1,97 kN
Basic dynamic load rating (C)	4,55 kN
Maximum Capacity / Filling Slot	No