



Bearing No. 6000LLB

C	8 mm
d	10 mm
D	26 mm
B	8 mm
Bore	0.394 Inch 10 Millimeter
Noun	Bearing
Weight	0,019 Kg
da max	13,5 mm
UNSPSC	31171504
r min.	0,3 mm
da min.	12 mm
ra max.	0,3 mm
series:	60
Da max.	24 mm
Category	Single Row Ball Bearing
Enclosure	2 Seals
Size (mm)	10x26x8
Inventory	0.0
Snap Ring	No
Width (mm)	8
bore type:	Round
maximum rpm:	34000 RPM
Weight / LBS	0.041
Cage Material	Steel
Inch - Metric	Metric
closure type:	Double Sealed
Product Group	B00308
bore diameter:	10 mm
Keyword String	Ball

overall width:	8 mm
cage material:	Steel
fillet radius:	0.3 mm
Bearing number	6000LLB
Enclosure Type	Non-Contact Seal
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Long Description	10MM Bore; 26MM Outside Diameter; 8MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	1.024 Inch 26 Millimeter
Outer Race Width	0.315 Inch 8 Millimeter
bearing material:	High Carbon Chrome Steel
outer ring width:	8 mm
inner ring width:	8 mm
Manufacturer Name	NTN
Weight / Kilogram	0.019
precision rating:	ISO Class 0
outside diameter:	26 mm
Bore Diameter (mm)	10
Internal Clearance	C0-Medium
snap ring included:	Without Snap Ring
Outer Diameter (mm)	26
internal clearance:	CN
Minimum Buy Quantity	N/A

static load capacity:	1960 N
maximum rpm (grease):	29000 rpm
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	4550 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6000LLB/2AS
Internal Special Features	No
(Grease) Lubrication Speed	29 000 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic dynamic load rating (C)	4,55 kN
Basic static load rating (C0)	1,96 kN
Maximum Capacity / Filling Slot	No