



Bearing No. 6000NR

f	0,84 mm
r	0.3
d	10 mm
D	26 mm
B	8 mm
C	8 mm
a	1,35 mm
b	0,87 mm
D2	28,7 mm
B_	8
Cy	1.9
ra	0.3
C0	1.97
fo	12.4
D_	26
D1	24,5 mm
rn	0,3 mm
Z_	7
Dx	29.4
ro	0.2
DE_	22.762
DA_	4.762
SRI	2.46
D_a	24
SRE	2.67
DI_	13.238
SRIN	-0.015
yobi	6000NR
SBRG	10
bomp	0

SREX	0.015
KBRG	6101
SREN	-0.015
SDM_	18
SRIX	0.015
mass	0.018
C_conv	4550
r min.	0,3 mm
da max	13 mm
ALPHA_	0
Weight	0,018 Kg
da min	12
LangID	1
GRS rpm	30000
Da max.	24 mm
hidYobi	6000NR
Oil rpm	36000
da min.	12 mm
r0 max.	0,2 mm
ra max.	0,3 mm
hidTable	ecat_NSRDGB
Size (mm)	10x26x8
Prod_Type3	DGBB_SR_NR_OT
Width (mm)	8
Bearing number	6000NR
Bore Diameter (mm)	10
Outer Diameter (mm)	26
(Oil) Lubrication Speed	36 000 r/min
(Grease) Lubrication Speed	30 000 r/min
Basic dynamic load rating (C)	4,55 kN
Basic static load rating	1,97 kN

(C0)	
------	--