



Bearing No. 6000VV

r	0.3
d	10 mm
D	26 mm
B	8 mm
C	8 mm
D_	26
B_	8
ra	0.3
C0	1.97
fo	12.4
Z_	7
DI_	13.238
SRE	2.67
D_a	24
DE_	22.762
DA_	4.762
SRI	2.46
SREN	-0.015
SBRG	10
SREX	0.015
KBRG	6151
Bore	0.394 Inch 10 Millimeter
mass	0.018
Noun	Bearing
SRIX	0.015
SRIN	-0.015
SDM_	18
bomp	0
yobi	6000VV

Weight	0,018 Kg
LangID	1
da max	13 mm
C_conv	4550
ALPHA_	0
da min	12
UNSPSC	31171504
r min.	0,3 mm
hidYobi	6000VV
ra max.	0,3 mm
GRS rpm	30000
Da max.	24 mm
da min.	12 mm
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Snap Ring	No
Size (mm)	10x26x8
Enclosure	2 Seals
Inventory	0.0
Width (mm)	8
bore type:	Round
Prod_Type3	DGBB_SR_VV
Weight / LBS	0.04
Product Group	B00308
Cage Material	Steel
closure type:	Double Sealed
Inch - Metric	Metric
Bearing number	6000VV
Keyword String	Ball
overall width:	8 mm
Enclosure Type	Non-Contact Seal
bore diameter:	10 mm

Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	1.024 Inch 26 Millimeter
Long Description	10MM Bore; 26MM Outside Diameter; 8MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	0.315 Inch 8 Millimeter
Manufacturer URL	http://www.nskamericas.com
Manufacturer Name	NSK
Weight / Kilogram	0.02
outside diameter:	26 mm
Bore Diameter (mm)	10
Internal Clearance	C0-Medium
Outer Diameter (mm)	26
internal clearance:	Normal Clearance
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6000VV
manufacturer upc number:	029176012181
Internal Special Features	No
(Grease) Lubrication Speed	30 000 r/min
Basic static load rating (C0)	1,97 kN
Basic dynamic load rating (C)	4,55 kN
Maximum Capacity /	No

Filling Slot	
--------------	--