



Bearing No. C 3192 KM + AOHX 3192 G

B	240 mm
D	760 mm
G	Tr 480x5
Size (mm)	760x440x285
Width (mm)	285
G ₁	43 mm
B ₁	285 mm
d ₁	440 mm
B ₁	285 mm
d ₂	559 mm
D ₁	679 mm
G ₁	480 mm
s ₁	51 mm
d ₁	440 mm
Bearing number	C 3192 KM + AOHX 3192 G
Limiting speed	800 r/min
Reference speed	600 r/min
Bore Diameter (mm)	760
r _a max.	6 mm
C _a min.	4.2 mm
D _a max.	728 mm
D _a min.	651 mm
d _a max.	603 mm
d _a min.	477 mm
s ₁ max.	51 mm
Outer Diameter (mm)	440
D _a - min.	651 mm
C _a - min.	4.2 mm

r_a - max.	6 mm
d_a - max.	603 mm
d_a - min.	477 mm
$r_{1,2}$ min.	7.5 mm
D_a - max.	728 mm
B_2 ?	296 mm
D_1 ?	679 mm
d_2 ?	559 mm
Mass bearing + sleeve	480 kg
$r_{1,2}$ - min.	7.5 mm
Factor - k_2	0.105
Factor - k_1	0.108
Basic dynamic load rating C	6800 kN
Basic dynamic load rating - C	6800 kN
Fatigue load limit P_u	815 kN
Misalignment factor k_1	0.108
Fatigue load limit - P_u	815 kN
Basic static load rating C_0	12000 kN
Basic static load rating - C_0	12000 kN
Operating clearance factor k_2	0.105