



**Bearing No. 6000ZZE**

D	26 mm
d	10 mm
B	8 mm
C	8 mm
Noun	Bearing
Bore	0.394 Inch   10 Millimeter
Width	8 mm
UNSPSC	31171504
r min.	0.3 mm
Weight	0.019 Kg
da min.	12 mm
Da max.	24 mm
ra max.	0.3 mm
Category	Single Row Ball Bearing
ra (max)	0.3 mm
da (min)	12 mm
Da (max)	24 mm
Bore Size	10 mm
Factor fo	12.4
Inventory	0.0
Bore Type	Cylindrical Bore
Enclosure	2 Metal Shields
Snap Ring	No
Size (mm)	10x26x8
Width (mm)	8
Inch - Metric	Metric
Configuration	Single Row
Product Group	B00308
Cage Material	Steel

Keyword String	Ball
Other Features	Deep Groove
Bearing number	6000ZZE
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Long Description	10MM Bore; 26MM Outside Diameter; 8MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel
Outside Diameter	1.024 Inch   26 Millimeter
Radial Clearance	0.002 to 0.013 mm
Manufacturer URL	<a href="http://www.nachiamerica.com">http://www.nachiamerica.com</a>
Outer Race Width	0.315 Inch   8 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Weight / Kilogram	0
Manufacturer Name	NACHI
Internal Clearance	C0-Medium
Static Load Rating	1,970 N
Bore Diameter (mm)	10
Dynamic Load Rating	4,550 N
Outer Diameter (mm)	26
Minimum Buy Quantity	N/A
Fillet Radius/Chamfer	0.3 mm
Harmonized Tariff Code	8482.10.50.68
Limiting Speed - Grease	30,000 rpm
Internal Special Features	No
(Grease) Lubrication	30000 r/min

Speed	
Basic static load rating (C0)	1,97 kN
Basic dynamic load rating (C)	4,55 kN
Maximum Capacity / Filling Slot	No