



Bearing No. 239/900 CAK/W33 + OH 39/900 H

K	12 mm
b	22.3 mm
D	1180 mm
B	206 mm
Size (mm)	1180x850x206
Width (mm)	206
D ₁	1101 mm
B ₁	326 mm
B ₅	125 mm
B ₂	100 mm
d ₃	1030 mm
B ₁	326 mm
d ₁	850 mm
d ₂	996 mm
d ₁	850 mm
B ₂	100 mm
B ₅	125 mm
d ₃	1030 mm
Bearing number	239/900 CAK/W33 + OH 39/900 H
Limiting speed	450 r/min
Reference speed	240 r/min
Bore Diameter (mm)	1180
r _a max.	5 mm
B _a min.	30 mm
D _a max.	1157 mm
d _b min.	924 mm
d _a max.	996 mm
Outer Diameter (mm)	850

d_a - max.	996 mm
Calculation factor e	0.15
$r_{1,2}$ min.	6 mm
r_a - max.	5 mm
B_a - min.	30 mm
D_a - max.	1157 mm
d_b - min.	924 mm
D_1 ?	1101 mm
d_2 ?	996 mm
Mass bearing + sleeve	930 kg
Calculation factor - e	0.15
$r_{1,2}$ - min.	6 mm
Basic dynamic load rating C	7652 kN
Basic dynamic load rating - C	7652 kN
Fatigue load limit P_u	1000 kN
Calculation factor Y_1	4.5
Calculation factor Y_2	6.7
Calculation factor Y_0	4.5
Calculation factor - Y_2	6.7
Calculation factor - Y_1	4.5
Fatigue load limit - P_u	1000 kN
Basic static load rating C_0	17000 kN
Basic static load rating - C_0	17000 kN