



Bearing No. NUP314EM

r	2.1
D	150 mm
C	35 mm
S	1,5 mm
B	35 mm
d	70 mm
Fw	89 mm
Z_	13
r1	2.1
da	81
C0	222
ra	2
rb	2
B_	35
D_	150
DA_	22
DE_	133
DI_	89
yobi	NUP314EM
mass	3.21
SDM_	111
KBRG	4165
SBRG	3
db min	81 mm
C_conv	205000
Db max	139 mm
r min.	2,1 mm
ALPHA_	0
LangID	1
dd min	100

dc min	92
Weight	3,09 Kg
db max	86
da min.	81 mm
D_a max	139
r1 min.	2,1 mm
rb max.	2 mm
TSR rpm	4800
Da max.	139 mm
GRS rpm	4000
Oil rpm	5000
ra max.	2 mm
hidYobi	NUP314EM
db max.	86 mm
hidTable	ecat_NSCLDR
Macha rpm	8000
Size (mm)	70x150x35
Prod_Type3	CRB_SR_NUP
Width (mm)	35
Bearing number	NUP314EM
Bore Diameter (mm)	70
Outer Diameter (mm)	150
(Grease) Lubrication Speed	4000 r/min
Basic static load rating (C0)	222 kN
Basic dynamic load rating (C)	205 kN