



Bearing No. C 41/560 K30MB + AOH 241/560 G

B	355 mm
D	920 mm
G	Tr 600x6
Size (mm)	920x530x393
Width (mm)	393
G ₁	38 mm
B ₁	393 mm
d ₁	530 mm
B ₁	393 mm
d ₂	664 mm
D ₁	802 mm
G ₁	600 mm
s ₁	23 mm
d ₁	530 mm
Bearing number	C 41/560 K30MB + AOH 241/560 G
Limiting speed	500 r/min
Reference speed	380 r/min
Bore Diameter (mm)	920
r _a max.	6 mm
C _a min.	13.8 mm
D _a max.	888 mm
D _a min.	770 mm
d _a max.	663 mm
d _a min.	592 mm
s ₁ max.	23 mm
Outer Diameter (mm)	530
D _a - min.	770 mm
C _a - min.	13.8 mm

r_a - max.	6 mm
d_a - max.	663 mm
d_a - min.	592 mm
$r_{1,2}$ min.	7.5 mm
D_a - max.	888 mm
B_2 ?	417 mm
D_1 ?	802 mm
d_2 ?	664 mm
Mass bearing + sleeve	989 kg
$r_{1,2}$ - min.	7.5 mm
Factor - k_2	0.101
Factor - k_1	
Basic dynamic load rating C	10400 kN
Basic dynamic load rating - C	10400 kN
Fatigue load limit P_u	1270 kN
Misalignment factor k_1	0
Fatigue load limit - P_u	1270 kN
Basic static load rating C_0	19600 kN
Basic static load rating - C_0	19600 kN
Operating clearance factor k_2	0.101