



Bearing No. 6002DDU

r	0.3
d	15 mm
D	32 mm
B	9 mm
C	9 mm
D_	32
B_	9
ra	0.3
C0	2.83
fo	13.9
Z_	9
SRI	2.46
SRE	2.52
D_a	30
DA_	4.762
DI_	18.738
DE_	28.262
SREX	0.03
SBRG	10
KBRG	6161
Bore	0.591 Inch 15 Millimeter
mass	0.031
SRIX	0.015
Noun	Bearing
SRIN	-0.015
SREN	0
SDM_	23.5
yobi	6002DDU
bomp	0

Width	0.512 Inch 13 Millimeter
da min	17
UNSPSC	31171504
C_conv	5600
r min.	0,3 mm
Weight	0,031 Kg
ALPHA_	0
LangID	1
da max	19 mm
hidYobi	6002DDU
Da max.	30 mm
GRS rpm	15000
Preload	Medium
ra max.	0,3 mm
da min.	17 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Inventory	0.0
Size (mm)	15x32x9
Snap Ring	No
Enclosure	2 Seals
Width (mm)	9
Prod_Type3	DGBB_SR_DD
Weight / LBS	0.06801
Flush Ground	Yes
Contact Angle	25 Degree
Raceway Style	1 Rib Outer Ring
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Bearing number	6002DDU
Keyword String	Ball

Enclosure Type	Contact Seal
Other Features	Deep Groove Rubber Seal
Precision Class	ABEC 1 ISO P0
Material - Ball	Steel
Rolling Element	Ball Bearing
Long Description	15MM Bore; 32MM Outside Diameter; 9MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage; C
Inner Race Width	0 Inch 0 Millimeter
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	0.354 Inch 9 Millimeter
Outside Diameter	1.26 Inch 32 Millimeter
Weight / Kilogram	0.03
Manufacturer Name	NSK
Bore Diameter (mm)	15
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Outer Diameter (mm)	32
Mounting Arrangement	Universal
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6002DDU
Internal Special Features	No
(Grease) Lubrication Speed	15 000 r/min

Basic static load rating (C0)	2,83 kN
Basic dynamic load rating (C)	5,6 kN
Maximum Capacity / Filling Slot	No