



Bearing No. 6002N

a	2,06 mm
r	0.3
d	15 mm
D	32 mm
B	9 mm
C	9 mm
b	1,35 mm
fo	13.9
B_	9
ra	0.3
C0	2.83
D1	30,15 mm
D_	32
Z_	9
rn	0,3 mm
ro	0.4
DE_	28.262
SRI	2.46
D_a	30
DA_	4.762
SRE	2.52
DI_	18.738
yobi	6002N
mass	0.031
SBRG	10
bomp	0
KBRG	6101
SREX	0.03
SREN	0
SRIN	-0.015

SDM_	23.5
SRIX	0.015
ALPHA_	0
r min.	0,3 mm
C_conv	5600
da max	19 mm
da min	17
Weight	0,031 Kg
LangID	1
ra max.	0,3 mm
Da max.	30 mm
Oil rpm	28000
da min.	17 mm
r0 max.	0,4 mm
hidYobi	6002N
GRS rpm	24000
hidTable	ecat_NSRDGB
Size (mm)	15x32x9
Prod_Type3	DGBB_SR_N_OT
Width (mm)	9
Bearing number	6002N
Bore Diameter (mm)	15
Outer Diameter (mm)	32
(Oil) Lubrication Speed	28 000 r/min
(Grease) Lubrication Speed	24 000 r/min
Basic dynamic load rating (C)	5,6 kN
Basic static load rating (C0)	2,83 kN