



Bearing No. 28680/28622

e	0.4
d	55,562 mm
D	97,63 mm
T	24,608 mm
B	24,608 mm
C	19,446 mm
a	21,3 mm
Da	88 mm
B_	24.608
Db	92 mm
da	68 mm
Y0	0.82
db	62 mm
C0	129
D_	97.63
Z_	23
C_	19.446
Y1	1.5
DE_	85.206
SLR	18
D_a	88
DI_	68.195
DA1	9.237
DA2	8.283
CUP	0.27
DA_	8.762
D_b	92
RAr	173.558
SDM_	76.784
KBRG	3161

yobi	28680/28622
CONE	0.499
ALP21	30
ALP22	2
ALP23	0
BETA_	1
BET21	3
BET23	0
BET22	3
r min.	3,5 mm
LangID	1
Weight	0,769 Kg
ALPHA_	15.017
r1 min.	0,8 mm
ra max.	3,5 mm
Oil rpm	5000
outer r	0.8
hidYobi	28680/28622
GRS rpm	3600
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	0.8
ra1 max.	0,8 mm
Size (mm)	55.562x97.63x24.608
SHOG_yobi	28680R/28622R
Prod_Type3	TRBSR_ID_A
Width (mm)	24,608
Bearing number	28680/28622
Bore Diameter (mm)	55,562
Outer Diameter (mm)	97,63
Calculation factor (e)	0,4

(Oil) Lubrication Speed	5000 r/min
Calculation factor (Y0)	0,82
(Grease) Lubrication Speed	3600 r/min
Basic static load rating (C0)	129 kN
Basic dynamic load rating (C)	89 kN