



### Bearing No. 6002ZZ

|                  |   |
|------------------|---|
| D                | 32 mm   |
| d                | 15 mm   |
| B                | 9 mm  |
| C                | 9 mm  |
| Bore             | 0.591 Inch   15 Millimeter                                  |
| Noun             | Bearing   |
| r min.           | 0,3 mm  |
| da max           | 18,5 mm   |
| UNSPSC           | 31171504  |
| Weight           | 0,03 Kg   |
| ra max.          | 0,3 mm  |
| Da max.          | 30 mm   |
| da min.          | 17 mm   |
| Category         | Single Row Ball Bearing                                     |
| Enclosure        | 2 Metal Shields   |
| Inventory        | 0.0   |
| Size (mm)        | 15x32x9   |
| Snap Ring        | No  |
| Width (mm)       | 9   |
| Weight / LBS     | 0.0661  |
| Inch - Metric    | Metric  |
| Cage Material    | Steel   |
| Product Group    | B00308  |
| Other Features   | Deep Groove   |
| Bearing number   | 6002ZZ  |
| Keyword String   | Ball  |
| Precision Class  | ABEC 1   ISO P0   |
| Rolling Element  | Ball Bearing  |
| Manufacturer URL | <a href="http://www.koyousa.com">http://www.koyousa.com</a> |
|                  |   |

|                                 |  |
|---------------------------------|--|
| Outer Race Width                | 0.354 Inch   9 Millimeter  |
| Outside Diameter                | 1.26 Inch   32 Millimeter  |
| Long Description                | 15MM Bore; 32MM Outside Diameter; 9MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel |
| Inner Race Width                | 0 Inch   0 Millimeter  |
| Manufacturer Name               | KOYO   |
| Weight / Kilogram               | 0.033  |
| Internal Clearance              | C0-Medium  |
| Bore Diameter (mm)              | 15   |
| Outer Diameter (mm)             | 32   |
| Minimum Buy Quantity            | N/A  |
| Harmonized Tariff Code          | 8482.10.50.68  |
| Internal Special Features       | No   |
| (Grease) Lubrication Speed      | 23000 r/min  |
| Basic static load rating (C0)   | 2,85 kN  |
| Basic dynamic load rating (C)   | 5,6 kN   |
| Maximum Capacity / Filling Slot | No   |