



**Bearing No. RTUE70**

|               |                               |
|---------------|-------------------------------|
| N             | 41 mm                         |
| A             | 70 mm                         |
| T             | 110 mm                        |
| L             | 214 mm                        |
| H             | 166 mm                        |
| d             | 70 mm                         |
| L2            | 20 mm                         |
| S1            | 44,5 mm                       |
| N2            | 70 mm                         |
| A2            | 50 mm                         |
| N1            | 35 mm                         |
| L3            | 120 mm                        |
| L1            | 135 mm                        |
| H1            | 151 mm                        |
| B1            | 66 mm                         |
| A1            | 25 mm                         |
| d3            | 96 mm                         |
| Noun          | Bearing                       |
| Bore          | 2.756 Inch   70<br>Millimeter |
| UNSPSC        | 31171533                      |
| Weight        | 6,82 Kg                       |
| Category      | Take Up Units                 |
| Inventory     | 0.0                           |
| Slot Width    | 0.984 Inch   25<br>Millimeter |
| Thread (Q)    | Rp1/8                         |
| Weight / LBS  | 15.876                        |
| Product Group | M06110                        |
| Inch - Metric | Metric                        |
| Housing Style | Unit Only                     |

|                               |  |
|-------------------------------|--|
| Keyword String                | Take Up  |
| Other Features                | Single Row   Spherical   Double Land Riding Rubber Contact Seal  |
| Bearing number                | RTUE70   |
| Mounting Method               | Eccentric Collar   |
| Rolling Element               | Ball Bearing   |
| Housing Material              | Cast Iron  |
| Long Description              | Take Up Bearing Only; 70MM Bore; 25MM Slot Width; 151MM Slot to Slot Distance; Ball Bearing; Unit Only; Eccentric Collar Mount; GE70KRRB Insert Part; Cast Iron Housing Material |
| Manufacturer URL              | <a href="http://www.ina.com">http://www.ina.com</a>  |
| Weight / Kilogram             | 8.466  |
| Manufacturer Name             | SCHAEFFLER GROUP   |
| Insert Part Number            | GE70KRRB   |
| Bore Diameter (mm)            | 70   |
| Minimum Buy Quantity          | N/A  |
| Component Description         | Take Up Bearing Only   |
| Slot to Slot Distance         | 5.945 Inch   151 Millimeter  |
| Harmonized Tariff Code        | 8483.20.40.40  |
| Compatible Take Up Frame      | Not Specified  |
| Adjustment Travel Length      | 0  |
| Basic dynamic load rating (C) | 62 kN  |