



## Bearing No. 53212

r	1
C	71.5
d	60 mm
D	95 mm
T	28 mm
A	32,5 mm
R	72 mm
R_	72
Z_	17
D_	95
B_	28
ra	1
C0	169
da	81
D1	62 mm
T3	28
A_	32.5
d1	95 mm
SRE	6.85
DA_	12.7
SRI	6.85
D_1	62
D_a	74
KBRG	5121
SREX	0.05
SDM_	77.5
yobi	53212
mass	0.731
SRIX	0.05
SRIN	0

SREN	0
Noun	Bearing
LangID	1
Height	1.102 Inch   28 Millimeter
Bore 2	2.441 Inch   62 Millimeter
Bore 1	2.362 Inch   60 Millimeter
UNSPSC	31171552
r min.	1 mm
Weight	0,731 Kg
Banded	No
series:	52300
da min.	81 mm
Da max.	74 mm
ra max.	1 mm
GRS rpm	2000
Oil rpm	3000
hidYobi	53212
hidTable	ecat_NSSDTB
Category	Thrust Ball Bearings
Inventory	0.0
Size (mm)	60x95x28
Width (mm)	28
Prod_Type3	TB_SD_WAS
race type:	Flat
Weight / LBS	1.61158
maximum rpm:	3000 rpm
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
Keyword String	Ball Thrust

bore diameter:	60 mm
Thrust Bearing	Yes
Other Features	Single Row   With Aligning Seat
Bearing number	53212
overall width:	31 mm
cage material:	Steel Cage
fillet radius:	1 mm
Rolling Element	Ball Bearing
Precision Class	Non-Precision
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Long Description	60MM Bore 1; 62MM Bore 2; 95MM Outside Diameter; 28MM Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; Non-Precision
Outside Diameter	3.74 Inch   95 Millimeter
precision rating:	ABEC1, P0
Weight / Kilogram	0.85
Manufacturer Name	NSK
outside diameter:	95 mm
Bore Diameter (mm)	60
Outer Diameter (mm)	95
separable or banded:	Separable
Minimum Buy Quantity	N/A
thrust bearing type:	Single-Direction
Component Description	Roller Assembly Plus Raceways
static load capacity:	38000 lbf
dynamic load capacity:	16100 lbf
Harmonized Tariff Code	8482.10.50.08
outside diameter design:	Straight

Manufacturer Item Number	53212
(Grease) Lubrication Speed	2000 r/min
Single or Double Direction	Single Direction
operating temperature range:	Maximum of +120 °C
Basic dynamic load rating (C)	71,5 kN
Basic static load rating (C0)	169 kN
Overall Height with Aligning Washer	0 Inch   0 Millimeter