



Bearing No. 53212 + U 212

s	32.5 mm
R	72 mm
d	60 mm
D	95 mm
H	28 mm
C	9 mm
Size (mm)	95x60x28
Width (mm)	28
D ₁	62 mm
D ₃	100 mm
H ₁	31 mm
D ₂	78 mm
d ₁	95 mm
H ₁	31 mm
D ₃	100 mm
D ₂	78 mm
Limiting speed	3600 r/min
Bearing number	53212 + U 212
Reference speed	2600 r/min
d _a min.	81 mm
D _a max.	78 mm
r _a max.	1 mm
Bore Diameter (mm)	95
Outer Diameter (mm)	60
r _a - max.	1 mm
D _a - max.	78 mm
r _{1,2} min.	1 mm
d _a - min.	81 mm
Minimum load factor A	0.12

d_1 ?	95 mm
D_1 ?	62 mm
$r_{1,2}$ - min.	1 mm
Minimum load factor - A	0.12
Basic dynamic load rating C	59.2 kN
Basic dynamic load rating - C	59.2 kN
Fatigue load limit P_u	5.1 kN
Fatigue load limit - P_u	5.1 kN
Basic static load rating C_0	140 kN
Basic static load rating - C_0	140 kN
Mass bearing (including seat washer where applicable)	0.82 kg