



**Bearing No. 53213 + U 213**

s	40 mm
R	80 mm
d	65 mm
D	100 mm
H	28.7 mm
C	9 mm
Size (mm)	100x65x28.7
Width (mm)	28,7
$D_1$	67 mm
$D_3$	105 mm
$H_1$	32 mm
$D_2$	82 mm
$d_1$	100 mm
$H_1$	32 mm
$D_3$	105 mm
$D_2$	82 mm
Limiting speed	3600 r/min
Bearing number	53213 + U 213
Reference speed	2600 r/min
$d_a$ min.	86 mm
$D_a$ max.	82 mm
$r_a$ max.	1 mm
Bore Diameter (mm)	100
Outer Diameter (mm)	65
$r_a$ - max.	1 mm
$D_a$ - max.	82 mm
$r_{1,2}$ min.	1 mm
$d_a$ - min.	86 mm
Minimum load factor A	0.14

$d_1$ ?	100 mm
$D_1$ ?	67 mm
$r_{1,2}$ - min.	1 mm
Minimum load factor - A	0.14
Basic dynamic load rating C	60.5 kN
Basic dynamic load rating - C	60.5 kN
Fatigue load limit $P_u$	5.5 kN
Fatigue load limit - $P_u$	5.5 kN
Basic static load rating $C_0$	150 kN
Basic static load rating - $C_0$	150 kN
Mass bearing (including seat washer where applicable)	0.91 kg