



## Bearing No. 53215

R	90 mm
C	78
r	1
d	75 mm
D	110 mm
T	28,3 mm
A	49 mm
R_	90
B_	28.3
ra	1
C0	209
da	96
Z_	21
A_	49
T3	28.3
d1	110 mm
D_	110
D1	77 mm
D_1	77
DA_	12.7
SRI	6.85
SRE	6.85
D_a	89
SREN	0
SRIN	0
yobi	53215
SRIX	0.05
mass	1.27
SDM_	92.5
KBRG	5121

SREX	0.05
Noun	Bearing
Bore 2	3.031 Inch   77 Millimeter
Banded	No
UNSPSC	31171552
r min.	1 mm
LangID	1
Height	1.102 Inch   28 Millimeter
Weight	1,27 Kg
Bore 1	2.953 Inch   75 Millimeter
Oil rpm	2800
GRS rpm	1800
hidYobi	53215
ra max.	1 mm
Da max.	89 mm
da min.	96 mm
Category	Thrust Ball Bearings
hidTable	ecat_NSSDTB
Size (mm)	75x110x28.3
Inventory	0.0
Prod_Type3	TB_SD_WAS
Width (mm)	28,3
Weight / LBS	2.79987
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Bearing number	53215
Other Features	Single Row   With Aligning Seat
Thrust Bearing	Yes

Keyword String	Ball Thrust
Rolling Element	Ball Bearing
Precision Class	Non-Precision
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Long Description	75MM Bore 1; 77MM Bore 2; 110MM Outside Diameter; 28MM Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; Non-Precision
Outside Diameter	4.331 Inch   110 Millimeter
Weight / Kilogram	1.06
Manufacturer Name	NSK
Bore Diameter (mm)	75
Outer Diameter (mm)	110
Minimum Buy Quantity	N/A
Component Description	Roller Assembly Plus Raceways
Harmonized Tariff Code	8482.10.50.08
(Grease) Lubrication Speed	1800 r/min
Single or Double Direction	Single Direction
Basic static load rating (C0)	209 kN
Basic dynamic load rating (C)	78 kN
Overall Height with Aligning Washer	0 Inch   0 Millimeter