



Bearing No. 239/1180-B-K-MB

|                     |   |
|---------------------|---|
| m                   | 1340 kg / Weight                          |
| d                   | 1180 mm                                   |
| D                   | 1540 mm                                   |
| B                   | 272 mm                                    |
| e                   | 0,17                                      |
| Size (mm)           | 1180x1540x272                             |
| Width (mm)          | 272                                       |
| $n_s$               | 23,5 mm                                   |
| $Y_1$               | 4,05                                      |
| $Y_2$               | 6,04                                      |
| $D_1$               | 1438,3 mm                                 |
| $d_s$               | 12,5 mm                                   |
| $Y_0$               | 3,96                                      |
| $n_G$               | 370 1/min / Limiting speed                |
| $n_B$               | 178 1/min / Reference speed               |
| $C_r$               | 11300000 N / Dynamic load rating (radial) |
| $C_{Or}$            | 31000000 N / Static load rating (radial)  |
| Bearing number      | 239/1180-B-K-MB                           |
| $C_{ur}$            | 1760000 N                                 |
| $r_{min}$           | 7,5 mm                                    |
| $r_{a\ max}$        | 6 mm                                      |
| $d_{a\ min}$        | 1208 mm                                   |
| $D_{a\ max}$        | 1512 mm                                   |
| Bore Diameter (mm)  | 1180                                      |
| Outer Diameter (mm) | 1540                                      |

