



Bearing No. 53218

R	100 mm
C	114
r	1.1
d	90 mm
D	135 mm
T	38,5 mm
A	45 mm
R_	100
B_	38.5
ra	1
C0	310
da	117
Z_	20
A_	45
T3	38.5
d1	135 mm
D_	135
D1	93 mm
D_1	93
DA_	15.875
SRI	8.57
SRE	8.57
D_a	108
SREN	0
SRIN	0
yobi	53218
SRIX	0.065
mass	1.89
SDM_	112.5
KBRG	5121

SREX	0.065
Noun	Bearing
Bore 1	3.543 Inch 90 Millimeter
Bore 2	3.661 Inch 93 Millimeter
Banded	No
UNSPSC	31171552
r min.	1,1 mm
LangID	1
Height	1.535 Inch 39 Millimeter
Weight	1,89 Kg
GRS rpm	1400
hidYobi	53218
Oil rpm	2200
ra max.	1 mm
Da max.	108 mm
da min.	117 mm
Category	Thrust Ball Bearings
hidTable	ecat_NSSDTB
Size (mm)	90x135x38.5
Inventory	0.0
Prod_Type3	TB_SD_WAS
Width (mm)	38,5
Weight / LBS	4.16674
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Bearing number	53218
Other Features	Single Row With Aligning Seat
Thrust Bearing	Yes

Keyword String	Ball Thrust
Rolling Element	Ball Bearing
Precision Class	Non-Precision
Manufacturer URL	http://www.nskamericas.com
Long Description	90MM Bore 1; 93MM Bore 2; 135MM Outside Diameter; 39MM Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; Non-Precision
Outside Diameter	5.315 Inch 135 Millimeter
Weight / Kilogram	2.19
Manufacturer Name	NSK
Bore Diameter (mm)	90
Outer Diameter (mm)	135
Minimum Buy Quantity	N/A
Component Description	Roller Assembly Plus Raceways
Harmonized Tariff Code	8482.10.50.08
(Grease) Lubrication Speed	1400 r/min
Single or Double Direction	Single Direction
Basic static load rating (C0)	310 kN
Basic dynamic load rating (C)	114 kN
Overall Height with Aligning Washer	0 Inch 0 Millimeter