



Bearing No. 53224

R	125 mm
C	141
r	1.1
d	120 mm
D	170 mm
T	40,8 mm
A	61 mm
R_	125
B_	40.8
ra	1
C0	430
da	150
Z_	23
A_	61
T3	40.8
d1	170 mm
D_	170
D1	123 mm
D_1	123
DA_	17.462
SRI	9.4
SRE	9.4
D_a	140
SREN	0
SRIN	0
yobi	53224
SRIX	0.065
mass	2.94
SDM_	145
KBRG	5121

SREX	0.065
Noun	Bearing
Weight	2,94 Kg
Height	1.606 Inch 40.8 Millimeter
Banded	No
UNSPSC	31171552
r min.	1,1 mm
LangID	1
Bore 1	4.724 Inch 120 Millimeter
Bore 2	4.843 Inch 123 Millimeter
GRS rpm	1200
hidYobi	53224
Oil rpm	1800
ra max.	1 mm
Da max.	140 mm
da min.	150 mm
Category	Thrust Ball Bearings
hidTable	ecat_NSSDTB
Size (mm)	120x170x40.8
Inventory	0.0
Prod_Type3	TB_SD_WAS
Width (mm)	40,8
Weight / LBS	6.48159
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Bearing number	53224
Other Features	Single Row With Aligning Seat
Thrust Bearing	Yes

Keyword String	Ball Thrust
Rolling Element	Ball Bearing
Precision Class	Non-Precision
Manufacturer URL	http://www.nskamericas.com
Long Description	120MM Bore 1; 123MM Bore 2; 170MM Outside Diameter; 40.8MM Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; Non-Precision
Outside Diameter	6.693 Inch 170 Millimeter
Weight / Kilogram	3.46
Manufacturer Name	NSK
Bore Diameter (mm)	120
Outer Diameter (mm)	170
Minimum Buy Quantity	N/A
Component Description	Roller Assembly Plus Raceways
Harmonized Tariff Code	8482.10.50.08
(Grease) Lubrication Speed	1200 r/min
Single or Double Direction	Single Direction
Basic static load rating (C0)	430 kN
Basic dynamic load rating (C)	141 kN
Overall Height with Aligning Washer	0 Inch 0 Millimeter