



Bearing No. NUP240EM

r	4
D	360 mm
C	58 mm
S	2,2 mm
B	58 mm
d	200 mm
Fw	243 mm
Z_	19
r1	4
da	216
C0	1060
ra	3
rb	3
B_	58
D_	360
DA_	40
DE_	323
DI_	243
yobi	NUP240EM
mass	27.8
SDM_	283
KBRG	4165
SBRG	2
db min	216 mm
C_conv	765000
Db max	344 mm
r min.	4 mm
ALPHA_	0
LangID	1
dd min	261

dc min	247
Weight	27,4 Kg
db max	238
da min.	216 mm
D_a max	344
r1 min.	4 mm
rb max.	3 mm
TSR rpm	1900
Da max.	344 mm
GRS rpm	1700
Oil rpm	2000
ra max.	3 mm
hidYobi	NUP240EM
db max.	238 mm
hidTable	ecat_NSCLDR
Macha rpm	3200
Size (mm)	200x360x58
Prod_Type3	CRB_SR_NUP
Width (mm)	58
Bearing number	NUP240EM
Bore Diameter (mm)	200
Outer Diameter (mm)	360
(Grease) Lubrication Speed	1700 r/min
Basic static load rating (C0)	1060 kN
Basic dynamic load rating (C)	765 kN